

HIGH VOLUME EXTINGUISHER

This weight-optimized and compact high performance system generates a far reaching stream of CAFS foam, for fighting medium sized fires of class A + B with area-covering effect. It can be applied fast and easily and thanks to its large wheels it may even be moved over stairways. Sturdy and easy to maintain, it can be refilled by the user in a quick and economic way. Professionals around the world choose this system as an alternative to stationary extinguishing systems, because of its excellent reliability and unbeatable price-performance ratio.



APPROVED
FOR



- quick and easy to refill
- low space requirement
- integrated pressure gauge
- 10 m hose, large scope of action
- extra high jet range, long duration
- large capacity for medium size fires
- movable over rough ways and stairs
- operable in horizontal position



TECHNICAL DATA

APPROVED
FOR



Description:

Highly compact extinguisher with large volume for professional use in widely ramified spaces. Equipped with steel pressure bottle (6.8 liter/300 bar), pressure reducer with safety valve and gauge. 10 meters highly flexible, heat-resistant hose and hook wrench for top lid included.

SPECS

filling capacity	50 liters
operation pressure	22 bar, constant
propellant	air, 300 bar/6.8 l bottle
duration	app. 78 sec.
jet range	up to 18 m
flow rate	0.65 l / sec.
extinguishing units	65
temp. range *	5 to 60° C
fire class (EN1866)	in preparation
electrical systems	max. 1000 volts at 4 m
weight (empty)	app. 48 kg
weight (filled)	app. 98 kg
height	109 cm
length	55 cm
track width	42 cm
certification	SQ 60/15

* with frost proof extinguishing agent: -25 to 60°C



optional accessories:



variable jet gun

with high performance
nozzle, steplessly actuation
and lockable trigger

Available on request:

- CFRP pressure bottle for weight reduction
- statutory inspection after 1-5-10 years

Please ask

